

Product Description

Chennai paints Red Oxide Metal primer is a solvent –based economical anti-corrosive protective primer for interior and exterior ferrous and non-ferrous metal work, including steel work, new, weathered and pre-treated zinc and galvanised iron. It can be applied on pre-treated aluminium.

<u>Technical Data</u>	
Product Type	Metal Primer Red oxide
Area of Application	Ferrous & Non Ferrous substrates. (Structural (Steel and equipment exposed to exterior/ interior Weather conditions and corrosive environment)
Finish	Smooth and Matt
Shades	Red
Viscosity	100 + 10 secs in B4 cup
Application Viscosity	For Brushing/spraying 40-45 secs in B4 cup (i.e.) 15 % of dilution by volume (Do not over thin Stir well and strain before use)
Specific Gravity	1.400 per lt.
Thinner	Mineral Turpentine Oil.
Application	By brush or spray.
Wet Opacity	8 to 10 sq mtr per lt
Drying Time	surface dry 30-40 mts / Hard dry 8-10 hours.
Recoating time	after 8 hours (depending upon the room temperature and Humidity)
Hazard Class	Flammable
Safety Precaution	Work in a well ventilated place wearing all the safety Clothing like overalls and gloves.
Available In	20, 10, 4, 1 and 500ml tins (Metal Tins)


Storage	Cool and dry place.
Discarding	Dispose the metal tins in land filling and do not drain it Any water channel.

Direction for Use:

Make sure that the surface to be painted is free from moisture, loose particles, oil, greese and rust. Degreasing and derusting can be done by appropriate treatment. Apply by brush or spray after adjusting the viscosity using Mineral Turpentine Oil.

To achieve the best result allow the primer coat to dry for at least 8 hour and sand it with emery paper no 180 before applying the subsequent coat.

DISCLAIMER; The product data information & application details are based on our current knowledge and experience, in view of the many factors that may affect processing and application of our product, these data given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quantity of other materials used and on-site workmanship are factors beyond our control. There are no expressed or implied guarantee/warranty as to the results obtained. The company does not assume liability or any consequential damage for unsatisfactory results, arising from the use of our products.

	<p>Chennai Paints Old No.365, New No.200-A, Madhavaram High Road, Madhavaram, Chennai – 600 060. INDIA</p>	<p>Tex : +91 (44) 25581664 Fax : +91 (44) 25581665 E-mail : chennaipaints@gmail.com info@chennaipaints.com www.chennaipaints.com</p>	<ul style="list-style-type: none"> • Anti Termite Treatment • Tile Adhesive & Grouts • Construction Chemicals • Waterproofing compounds • Interior & Exterior Wall Putty • Waterproof Cement Paint & Primers
<p>Estd : 2007</p>			